

Data Section

Transfer Rate	READ	DVD-ROM	8.7-21.1 Mbytes/sec (6.6-16x CAV)	
		DVD-R	8.7-21.1 Mbytes/sec (6.6-16x CAV)	
		DVD+R	8.7-21.1 Mbytes/sec (6.6-16x CAV)	
		DVD-R DL	6.6-15.8 Mbytes/sec (5-12x CAV)	
		DVD+R9	6.6-15.8 Mbytes/sec (5-12x CAV)	
		DVD-RW	6.6-17.2 Mbytes/sec (5-13x CAV)	
		DVD+RW	6.6-17.2 Mbytes/sec (5-13x CAV)	
		DVD-RAM *	7.9-15.8 Mbytes/sec (6.0-12x PCAV)	
		CD-ROM, CD-R	3000-7200 Kbytes/sec (20-48x CAV)	
		CD-RW, CD-ROM XA	2550-6000 Kbytes/sec (17-40x PCAV)	
		CD-DA	2550-6000 Kbytes/sec (17-40x PCAV)	
	WRITE	DVD+R	13.2-31.7 Mbytes/sec (24x)	
		<i>supported speeds</i>	24/20x/18x/16x/13x/12x/8x/6x/4x/2.4x	
		DVD+R9	6.6-15.8 Mbytes/sec (12x)	
		<i>supported speeds</i>	12x/8x/6x/4x/2.4x	
		DVD+RW	7.9-10.6 Mbytes/sec (8x)	
		<i>supported speeds</i>	8x/6x/4x/2.4x	
		DVD-R	13.7-33 Mbytes/sec (24x)	
		<i>supported speeds</i>	24/20x/18x/16x/13x/12x/8x/6x/4x/2x	
		DVD-R DL	6.-15.8 Mbytes/sec (12x)	
		<i>supported speeds</i>	12x/8x/6x/4x/2x	
		DVD-RW	7.9 Mbytes/sec (6x)	
		<i>supported speeds</i>	6x/4x/2x/1x	
		DVD-RAM*	7.9-15.8 Mbytes/sec (12x)	
		<i>supported speeds</i>	12x/5x/3x/2x	
		CD-R	3000-7200 Kbytes/sec (48x)	
		<i>supported speeds</i>	48x/40x/32x/24x/16x/8x	
		CD-RW	2400-4800 Kbytes/sec (32x)	
		<i>supported speeds</i>	32x/24x/16x/10x/4x	
Write methods			DAO (disc at once), SAO (session at once), TAO (track at once) with zero gap, variable or fixed packet, multisession	
Access Time			DVD-ROM (1/3 stroke read, average)	160 msec
		CD-ROM (1/3 stroke read, average)	140 msec	
Compatibility		DVD-ROM, DVD-Video, DVD+R,DVD+R DL, DVD+RW, DVD-R, DVD-R DL, DVD-RW, DVD-RAM(Ver.2), CD-Audio, CD-ROM(modes 1 & 2), CD-ROM XA(mode 2, form 1 & form 2),VIDEO CD,CD-I (FMV) Photo CD(single/multiplesessions), CD Extra, CD-RW, CD-TEXT		
In compliance with		MultiRead, PC-2001, MS Vista		

General

Memory Buffer		2 MBytes
Interface		Serial ATA , max. 150 MByte/sec
Power Consumption		max. 31.5 VA , 5V 1.5A; 12V 2A
Dimensions (W x H x D)		148x42x170 mm
Weight		0.6 kg
Noise		52.5dB(A) max.
Storage temperature and humidity		-40° to 65° C, 5% to 95% RH, noncondensing
Operating temperature and humidity		5° to 50° C, 15% to 80% RH, noncondensing
Direct Label Print	AD-7261	LightScribe
	AD-7263	Labelflash
	AD-7260/AD-5260S	NO!
DVD-RAM*		All except AD-5260S

Above specifications are subject to change. Microsoft, Windows, and Windows Vista are registered trademarks Microsoft Corporation, Photo CD is a trademark of Kodak.